Product code

# SBA-100

Solid Base Angle Lintel - 100 x 100 x 6mm

Product datasheet

View product online

Solid Base Angles have been designed to support brickwork over windows & doors. The brickwork, mortar and lintel work together to form a composite beam with exceptional strength and load-carrying capacity. Genuine Galintel Hot Dip Galvanised lintels are 40% lighter than solid lintels (and 40% easier to carry) with a high strength to weight ratio.

| | |
|---|---|
| **Corrosion class** | |
| **Material** | Hot dipped galvanised |
| **Sizes** | 0.9m – 2.7m (7) |

## Features

- The original & unique profile provides a recess for mortar bedding on the vertical leg.
- The bonding of mortar, brickwork & steel lintel forms a composite beam of superior strength and load bearing capacity.
- 40% lighter than conventional steel lintels with a high strength to weight ratio.
- Fully Hot Dip Galvanised to AS/NZS4680.
- Achieves R3 Durability Rating to AS/NZS2699.3.
- Compliant with relevant Australian Building Codes & Australian Standards.
- Fully engineered and university tested.
- Australian designed and manufactured.
- Full product warranty.
- Stencilled.
- Labelled & bar coded.

## Technical details




Dimension drawing. Sizes are given as A.

### Sizes

| A |
|---|
| 0.9m |
| 1.2m |
| 1.5m |
| 1.8m |
| 2.1m |
| 2.4m |
| 2.7m |

### Corrosion characteristics

| | |
|---|---|
| | Hot dipped galvanised |

## Ordering information

Choose one option from each column to build the order code, then give us the code and the quantity you need.

Example order code

**SBA-100-0.9m**

| Product code | Size – A |
|---|---|
| **SBA-100**<br>Solid Base Angle Lintel - 100 x 100 x 6mm | **-0.9m**<br>**-1.2m**<br>**-1.5m**<br>**-1.8m**<br>**-2.1m**<br>**-2.4m**<br>**-2.7m** |