Product code

SBA-150

Solid Base Angle Lintel - 150 x 100 x 6mm

Product datasheet

View product online

Solid Base Angles have been designed to support brickwork over windows & doors. The brickwork, mortar and lintel work together to form a composite beam with exceptional strength and load-carrying capacity. Genuine Galintel Hot Dip Galvanised lintels are 40% lighter than solid lintels (and 40% easier to carry) with a high strength to weight ratio.

Corrosion class	
Material	Hot dipped galvanised
Sizes	1.8m – 4.0m (8)

Features

- The original & unique profile provides a recess for mortar bedding on the vertical leg.
- The bonding of mortar, brickwork & steel lintel forms a composite beam of superior strength and load bearing capacity.
- 40% lighter than conventional steel lintels with a high strength to weight ratio.
- Fully Hot Dip Galvanised to AS/NZS4680.
- Achieves R3 Durability Rating to AS/NZS2699.3.
- Compliant with relevant Australian Building Codes & Australian Standards.
- Fully engineered and university tested.
- Australian designed and manufactured.
- Full product warranty.
- Stencilled.
- Labelled & bar coded.

Technical details



Dimension drawing. Sizes are given as A.

Sizes

A
1.8m
2.1m
2.4m
2.7m
3.0m
3.3m
3.6m
4.0m

Corrosion characteristics

	Hot dipped galvanised

Ordering information

Choose one option from each column to build the order code, then give us the code and the quantity you need.

Example order code

SBA-150-1.8m

Product code	Size – A
SBA-150 Solid Base Angle Lintel - 150 x 100 x 6mm	**-1.8m** **-2.1m** **-2.4m** **-2.7m** **-3.0m** **-3.3m** **-3.6m** **-4.0m**